

700mm dia. Marker Buoy - Regulatory Style

The SL-B700RB Regulatory Style Buoy meets USA Federal, State and Local regulations for regulatory buoys, and is ideal for regulatory signage and for marking hazards, mooring fields and channels in in-land lakes and rivers, as well as coastal harbors.

FEATURES

- High visibility red, green, white or yellow as per IALA recommendations
- Mooring & lifting eye for additional strength & flexibility in installation
- Range of mooring equipment & chain available
- Excellent buoyancy & stability
- Mold-in graphics to suit customer requirements

SPECIFICATIONS:

General Characteristics

Product Life Expectancy

General Characteristics		
Available Colors	Orange, Red, Green, White, Yellow as per	
	IALA Recommendations	
Focal Plane Height (mm/inches)	1155 / 451/2	
Total Float Volume (ltrs/US gallon)	197 / 52	SLOV
Nominal Freeboard (mm/inches)	408 / 16	0101
Nominal Draft (mm/inches)	223 / 83/4	
Reserve Buoyancy (kgs/lbs)	60 / 132	NO
Maximum Mooring Load (kgs/lbs)	60 / 132	NU
Draft, Maximum (mm/inches)	470 / 181/2	
Freeboard, Minimum (mm/inches)	160 / 61/4	
Submergence (kg/cm, lb/inches)	3.8 / 21.6	WAKE
Physical Characteristics		WAIN
Material	Rotationally-molded UV-stabilized virgin	
	polyethylene,	
Wall Thickness (mm/inches)	7 / 1/4	
Ballast (kg/lbs)	20 / 44 internal concrete	
Filling	Closed-cell polyurethane foam	
Height (mm/inches)	1370 / 537/8	
Width (mm/inches)	700 / 271/2	
Mass (kg/lbs)	38 / 84	

Up to 12 years

To order or for more information contact us at:

Boatmoorings.com
PO Box 119
Milford, NH 03055
603-672-1751
dmerrill@boatmoorings.com