



Underwater Hammer Drill

HD45

The HD45 underwater hammer drill is a heavy duty underwater model designed concrete, rock and masonry drilling up to 2". Fluted drill bits require no water or air to clear holes. Ideal for drilling holes for setting anchor bolts. We also carry the drill bits you will need for reef pin installations.

- T-Handle with large on/off trigger for precise control
- Feathering on/off valve allows for increased control
- Drills 3/4" to 2" diameter holes up to 29" deep and core drills up to 4" diameter

Specifications

Chuck Capacity Up to 2" diameter or 4" core bit

Steel Capacity 736 Skil hex

Circuit Type Open Center

Flow Range 7-9 gpm / 26-34 lpm

Optimum Flow 8 gpm / 30 lpm

Working Pressure 1500-2000 psi / 105-140 bar

Full Relief Setting 2250 psi / 155 bar

Rotation Speed 0 - 300 rpm

Weight

(less tool bit) 49 lbs / 22.2 kg

Length 24." / 62.2 cm

Width

(at handles) 14" / 35 cm

Hydraulic Ports -8 SAE O-ring

Couplers

Varies with model
(See ordering information)

Hose Whips Yes

(3/8" NPT Male thread)

Features

- T-Handle with large on/off trigger for precise control
- Stainless Steel spools and fasteners
- Forward-Reverse with adjustable bit rotation speed
- Feathering on/off valve allows easy start and control
- Uses 736 Skil fluted carbide tipped drill bits - requires no water/air to clear holes
- Drills . to 2" diameter holes up to 29" deep and core drills up to 4" in diameter
- Operates in any position
- Trouble free drill steel latch retainer



To order or for more information contact us at:
Boatmoorings.com
PO Box 119
Milford, NH 03055
603-672-1751
dmerrill@boatmoorings.com