



Lift Bags:

Easy to Use

- Proprietary Plunger Dump Valve allows air control with a push of a button at the top of the bag and a lanyard at the bottom—vent air from above, beside, or below the lifting bag to achieve desired ascent rate.
- 1/4" NPT inflation port for remote filling, multiple bag coupling, or to install optional stainless steel quick disconnect.
- Ready for immediate use—factory-equipped with all necessary hardware

Multiple Applications

- Light salvage
- Object recovery
- Underwater construction
- Scientific research

Excellent Portability

- Fraction of the cost of a barge or crane
- Easy for a single diver to use
- Especially suited for remote locations
- Deployable from small craft

Fabric

- Urethane-coated nylon—high-strength and heavy-duty
- Superior abrasion resistance
- Resistant to most petro-chemicals
- UV-resistant
- Low maintenance requirements and easy to clean
- RF welded seams

Lift Straps Designed for Safety

- 6000lb. -load rated high strength resin-treated nylon webbing
- Sewn directly to the bottom of the bag
- Safe working ratio of 6:1

| Model | Lift Capacity | Diameter | Overall Height | Packaged Cubic Dimension | Weight |
|-------|---------------|--------------|----------------|--|---------------|
| C-100 | 120lb / 55kg | 16in / 0.41m | 30in / 0.77m | 14in x 10in x 6in / .36m x .26m x .15m | 5lb / 2.27kg |
| C-200 | 220lb / 100kg | 22in / 0.56m | 36in / 0.92m | 15in x 11in x 7in / .38m x .28m x .18m | 7lb / 3.18kg |
| C-500 | 550lb / 250kg | 29in / 0.74m | 43in / 1.07m | 15in x 11in x 7in / .38m x .28m x .18m | 12lb / 5.45kg |



To order or for more information contact us at:

Boatmoorings.com
PO Box 119
Milford, NH 03055
603-672-1751
dmerrill@boatmoorings.com