



SPECIFICATIONS

General Characteristics

Available Colors

Focal Plane Height (mm/inches)

Nominal Freeboard (mm/inches)

Nominal Draft (mm/inches)

Reserve Buoyancy (kgs/lbs)

Maximum Mooring Load (kgs/lbs)

Submergence (kg/cm, lb/inches)

Visual Area (m²/ft²)

Physical Characteristics

Material

Wall Thickness (mm/inches)

Ballast (kg/lbs)

Filling

Height (mm/inches)

Diameter (mm/inches)

Mass (kg/lbs)

Product Life Expectancy

SL-B1060

Red, Green, White, Yellow as per

IALA Recommendations

863 / 34

863 / 34

686 / 27

33 / 15

12 / 5

0.507 / 2.8

0.2 / 2.2

Rotationally-molded UV-stabilized
virgin polyethylene, 316-grade
mooring eye

9 / 3/8

22.6 / 50 internal counter-weight

Closed-cell polyurethane foam

1549 / 61

254 / 10

29 / 65

Up to 12 years

SL-B576

Black, Red, Green, White, Yellow as per IALA

Recommendations

914 / 36

914 / 36

1016 / 40

9 / 4

5 / 2

0.127 / 0.7

0.11 / 1.2

Rotationally-molded UV-stabilized virgin
polyethylene

7 / 1/4

6.8 / 15 internal counter-weight

Closed-cell polyurethane foam

1930 / 76

127 / 5

10.4 / 23

Up to 12 years



SL-B1060 Model



SL-B576 Model



Boatmoorings.com
PO Box 119
Milford, NH 03055
603-672-1751
dmerrill@boatmoorings.com