



Our Mooring Buoys are designed to offer customers long life and are suitable for a range of locations. This buoy has a unique recessed top section which allows connecting shackle to be protected from scratching the vessel.

The mooring buoy is available in 18" (457mm) and 24" (610mm) diameter and are rotationally-molded from UV-stabilized virgin polyethylene and are foam filled with closed-cell polyurethane to prevent water ingress in the unlikely event of damage to the outer layer.

They have a molded centre pipe with 2.6 inches (66mm) ID that will accept mooring chain of up to 5/8 inch (16mm) in diameter.

FEATURES

- Recessed shackle prevents scratching of vessel
- No painting ever
- Strong, polyethylene construction
- Clear identification with optional graphics
- Eco-friendly



SPECIFICATIONS

General Characteristics

Available Colors

Total Float Volume (US gallon/ltrs)

Reserve Buoyancy (lbs/kgs)

Note: 50% submergence in salt water

Draft, Maximum (inches/mm)

Freeboard, Minimum (inches/mm)

Submergence (lb/inches, kg/cm)

Will accommodate chain size up to (inches/mm)

Physical Characteristics

Material

Wall Thickness (inches/mm)

Filling

Height (inches/mm)

Width (inches/mm)

Mass (lbs/kg)

Product Life Expectancy

SL-MB-18

Red, Green, White, Yellow as per IALA

Recommendations

12¼ / 43.6

36 / 16.5

137/8 / 353

3 / 75

9 / 1.6

3/8 / 9.5

Rotationally-molded UV-stabilized virgin polyethylene

¼ / 7

Closed-cell polyurethane foam

167/8 / 428

175/8 / 446

13 / 5.9

Up to 12 years

SL-MB-24

Red, Green, White, Yellow as per IALA

Recommendations

287/8 / 109.5

101 / 46

18½ / 471

4 / 100

16 / 2.9

5/8 / 16

Rotationally-molded UV-stabilized virgin polyethylene

¼ / 7

Closed-cell polyurethane foam

22½ / 571

23¾ / 601

23 / 10.4

Up to 12 years

To order or for more information contact us at:

Boatmoorings.com

PO Box 119

Milford, NH 03055

603-672-1751

dmerrill@boatmoorings.com