



700mm dia. Marker Buoy - Regulatory Style

The SL-B700RB Regulatory Style Buoy meets USA Federal, State and Local regulations for regulatory buoys, and is ideal for regulatory signage and for marking hazards, mooring fields and channels in in-land lakes and rivers, as well as coastal harbors.

FEATURES

- High visibility red, green, white or yellow as per IALA recommendations
- Mooring & lifting eye for additional strength & flexibility in installation
- Range of mooring equipment & chain available
- Excellent buoyancy & stability
- Mold-in graphics to suit customer requirements

SPECIFICATIONS:

General Characteristics

Available Colors	Orange, Red, Green, White, Yellow as per IALA Recommendations
Focal Plane Height (mm/inches)	1155 / 45½
Total Float Volume (ltrs/US gallon)	197 / 52
Nominal Freeboard (mm/inches)	408 / 16
Nominal Draft (mm/inches)	223 / 8¾
Reserve Buoyancy (kgs/lbs)	60 / 132
Maximum Mooring Load (kgs/lbs)	60 / 132
Draft, Maximum (mm/inches)	470 / 18½
Freeboard, Minimum (mm/inches)	160 / 6¼
Submergence (kg/cm, lb/inches)	3.8 / 21.6

Physical Characteristics

Material	Rotationally-molded UV-stabilized virgin polyethylene,
Wall Thickness (mm/inches)	7 / ¼
Ballast (kg/lbs)	20 / 44 internal concrete
Filling	Closed-cell polyurethane foam
Height (mm/inches)	1370 / 53⅞
Width (mm/inches)	700 / 27½
Mass (kg/lbs)	38 / 84
Product Life Expectancy	Up to 12 years



To order or for more information contact us at:
 Boatmoorings.com
 PO Box 119
 Milford, NH 03055
 603-672-1751
 dmerrill@boatmoorings.com

